

1500 rpm - 50 Hz

1800 rpm - 60 Hz

JOHN DEERE

30-225 kVA

3^{ph}

Trifase
Three phase
Triphasé
Triásico



Aperto
Open frame
Sur châssis
Abierto



Raffreddato ad acqua
Water cooled
Refrroidi à eau
Refrigerado por agua



GP44A/J

MODELLO model	POTENZA-Power-kVA				MODELLO model	REG gov	MOTORE/Engine						SERBATOIO tank	DIMENSIONI dimensions			PESO weight	QUADRO ELETTRICO electric panel		INSONORIZZATO soundproof		
	CONT. PRP		MAX LTP				CIL. cyl.	CILIND. displac.	POTENZA power cv/hp		CONSUMO consump. 75% carico load l/h			L	L w	A h		Kg	MODELLO model		MODELLO model	
	50 Hz	60 Hz	50 Hz	60 Hz					50 Hz	60 Hz	50 Hz	60 Hz							MAN key start	AUTOM automatic start	S	SM

Gruppi elettrogeni non conformi con le normative europee Stage 2 - These Diesel Generator set models are not compliant with EU stage II Emission Legislation

GP33A/J-N	30	33	33	37	3029 DF 128	M	3	2900	42	47	5,9	6,5	70	1750	700	1100	720	M060	A060	T60 GP33S/J-N	/
GP44A/J-N	40	46	44	53	4039 DF 008	M	4	3900	54	66	7,5	9	70	1750	700	1100	880	M060	A060	T60 GP44S/J-N	/
GP88A/J-N	80	87	88	97	4045 TF 258	M	4	4500	111	122	14	16	100	2100	900	1300	1120	M070	A070	T65 GP88S/J-N	/
GP110A/J-N	100	120	110	133	4045 HF 158	M	4	4500	134	165	16,5	21	100	2100	900	1300	1250	M070	A070	T70 GP110S/J-N	/
GP140A/J-N	125	138	138	154	6068 TF 258	M	6	6800	161	190	18,5	24	140	2850	1000	1400	1420	M070	A070	T80 GP140S/J-N	/
GP165A/J-N	150	180	165	198	6068 HF 158	M	6	6800	205	251	26	32	140	2850	1000	1400	1520	M070	A070	T80 GP165S/J-N	/
GP198A/J-N	180	201	198	225	6068 HF 258	M	6	6800	245	282	31,3	36,1	150	3000	1100	1500	1610	M085	A085	T85 GP198S/J-N	/

Gruppi elettrogeni conformi con le normative europee Stage 2 - These Diesel Generator set models are compliant with EU stage II Emission Legislation

GP33A/J	30	/	33	/	3029TFU70	M	3	2900	42	/	6	/	70	1750	700	1100	720	M060	A060	T60 GP33S/J	/
GP44A/J	40	/	44	/	3029HFU70	M	4	3900	55,8	/	7,8	/	70	1750	700	1100	880	M060	A060	T60 GP44S/J	/
GP66A/J	60	/	66	/	4045TFU70	M	4	4500	81	/	11,5	/	100	2100	900	1300	950	M070	A070	T65 GP66S/J	/
GP88A/J	80	/	88	/	4045HFU72	E	4	4500	111	/	14,8	/	100	2100	900	1300	1120	M070	A070	T65 GP88S/J	/
GP110A/J	100	/	110	/	4045HFU79	E	4	4500	134	/	17,8	/	100	2100	900	1300	1250	M070	A070	T70 GP110S/J	/
GP140A/J	120	/	132	/	6068HFU72	E	6	6800	161	/	21,2	/	140	2850	1000	1400	1420	M070	A070	T80 GP140S/J	/
GP165A/J	150	/	165	/	6068HFU79	E	6	6800	205	/	25,3	/	140	2850	1000	1400	1520	M070	A070	T80 GP165S/J	/
GP198A/J	180	/	198	/	6068HFU74-01	E	6	6800	245	/	30,2	/	150	3000	1100	1500	1610	M085	A087	T85 GP198S/J	/
GP220A/J	200	/	220	/	6068HFU74-02	E	6	6800	278	/	34,2	/	160	3000	1100	1500	1560	M085	A087	T85 GP220S/J	T87 GP 220 SM/J