

1500 rpm - 50 Hz

1800 rpm - 60 Hz

DEUTZ

30-588 kVA

3^{ph}

Trifase
Three phase
Triphasé
Trifásico



Aperto
Open frame
Sur châssis
Abierto



Raffreddato ad acqua
Water cooled
Refrroidi à eau
Refrigerado por agua



GP505A/D

MODELLO model	POTENZA-Power-kVA				MOTORE/Engine								SERBATOIO tank	DIMENSIONI dimensions			PESO weight	QUADRO ELETTRICO electric panel		INSONORIZZATO soundproof		
	CONT. PRP		MAX LTP		MODELLO model	REG gov	CIL. cyl.	CILIND. displac.	POTENZA power cv/hp		CONSUMO consump. 75% carico load l/h			L	L w	A h		Kg	MODELLO model		MODELLO model	
	50 Hz	60 Hz	50 Hz	60 Hz					50 Hz	60 Hz	50 Hz	60 Hz							MAN key start	AUTOM automatic start	S	SM
GP33A/D	30	35,7	33	37,5	F4M 2011 (OLIO / OIL)	M	4	3108	41,2	47	5,4	6,6	70	1750	700	1100	650	M060	A060	T60 GP33S/D	/	
GP44A/D	40	48	44	50	BF4M 2011 (OLIO / OIL)	M	4	3108	54,6	62	7	8,3	70	1750	700	1100	710	M060	A060	T60 GP44S/D	/	
GP66A/D	59	/	65	/	BF4M 2011C (OLIO / OIL)	M	4	4038	71	/	10,4	/	100	2100	900	1300	960	M070	A070	T65 GP65S/D	/	
GP84A/D	76	81	81	92	BF4M 2012C	M	4	4039	95	108	12,3	15,6	100	2100	900	1300	1030	M070	A070	T65 GP84S/D	/	
GP110A/D	105	112	115	117	BF4M 1013EC	M	4	4764	133	140	18,2	19,9	100	2100	900	1300	1200	M070	A070	T70 GP110S/D	/	
GP145A/D	130	135	143	143	BF4M 1013FC	E	4	4764	163	170	18,9	22	140	2850	1000	1400	1280	M070	A070	T80 GP145S/D	/	
GP165A/D	150	171	165	180	BF6M 1013EC	M	6	7146	203	213	26,6	27,8	140	2850	1000	1400	1540	M070	A070	T85 GP165S/D	/	
GP176A/D	164	/	172	/	BF6M 1013EC	M	6	7146	203	/	26,6	/	140	2850	1000	1400	1540	M070	A070	T85 GP176S/D	/	
GP198A/D	180	207	198	232	BF6M1013FCG2	E	6	7146	243	275	31,6	35,4	150	3000	1100	1650	1580	M085	A087	T85 GP198S/D	/	
GP220A/D	200	226	220	250	BF6M 1013FCG3	E	6	7146	267	296	36,3	36,9	150	3000	1100	1650	1630	M085	A087	T85 GP220S/D	T87 GP220SM/D	
GP280A/D	250	254	275	286	TCD2013L06-4V	E	6	7146	328	336	42,9	45,3	150	3000	1100	1650	1750	M087	A087	T87 GP280S/D	T90 GP280SM/D	
GP330A/D	300	338	330	374	BF6M 1015C-G2	E	6	11906	409	438	58,2	54,5	300	3200	1300	2300	2180	M087	A087	/	T100SM GP330SM/D	
GP385A/D	350	/	385	/	BF6M 1015C-G3	E	6	11906	482	/	64	/	300	3200	1300	2300	2350	M087	A087	/	T100SM GP385SM/D	
*GP440A/D-N	400	419	440	462	BF8M 1015C-G1	E	8	15874	561	540	68,1	77,4	300	3200	1300	2200	2700	M087	A087	/	T110SM GP440SM/D-N	
GP505A/D	450	464	480	512	BF8M 1015C-G2	E	8	15874	556	593	74,3	74	320	3200	1300	2200	2800	M087	A087	T105 GP505S/D	T110SM GP505SM/D	
GP560A/D	500	536	550	588	BF8M 1015CP	E	8	15874	649	680	86	95,1	320	3200	1300	2200	2870	M087	A087	T105 GP505S/D	T110SM GP505SM/D	

* Gruppo elettrogeno non conforme con le normative europee Stage 2 - This Diesel Generator set model is not compliant with EU stage II Emission Legislation