

1500 rpm - 50 Hz
1800 rpm - 60 Hz
PERKINS

30-1125 kVA

3^{ph}

Trifase
Three phase
Triphasé
Trifásico



Aperto
Open frame
Sur châssis
Abierto



Raffreddato ad acqua
Water cooled
Refrroidi à eau
Refrigerado por agua

Perkins



GP700A/P

MODELLO model	POTENZA - Power - kVA				MOTORE/Engine								SERBATOIO tank	DIMENSIONI dimensions			PESO weight	QUADRO ELETTRICO electric panel		INSONORIZZATO soundproof			
	CONT. PRP		MAX LTP		MODELLO model	REG gov	CIL. cyl.	CILIND. displac.	POTENZA power cv/hp		CONSUMO consump. 75% carico load l/h			L	L	L		A	Kg	MODELLO model		MODELLO model	
	50 Hz	60 Hz	50 Hz	60 Hz					50 Hz	60 Hz	50 Hz	60 Hz								MAN key start	AUTOM automatic start	S	SM
									N.	cc	50 Hz	60 Hz								50 Hz	60 Hz	L	mm

Gruppi elettrogeni non conformi con le normative europee Stage 2 - These Diesel Generator set models are not compliant with EU stage II Emission Legislation

GP33A/P-N	30	35	33	38,5	1103A-33G	M	3	3300	41	62,5	5,4	6,6	70	1750	700	1100	780	M060	A060	T60 GP33S/P-N	/
GP44A/P-N	40	48	44	53	1103A-33TG1	M	3	3300	62	72,3	8,2	9,9	70	1750	700	1100	850	M060	A060	T60 GP44S/P-N	/
GP66A/P-N	60	68	66	85	1103A-33TG2	M	4	3300	81	90,5	10,4	12,5	100	2100	900	1300	940	M070	A070	T65 GP66S/P-N	/
GP88A/P-N	80	91,5	88	100,5	1104A-44TG2	M	4	4400	108	121	14	16,9	100	2100	900	1300	1050	M070	A070	T65 GP88S/P-N	/
GP145A/P-N	130	151	143	165,5	1006 TAG	E	6	5990	187	197	24,1	28,9	140	2850	1000	1400	1350	M070	A070	T80 GP145S/P-N	/
GP165A/P-N	150	/	165	/	1006 TAG2	E	6	5990	201	/	31	/	140	2850	1000	1400	1400	M070	A070	T85 GP165S/P-N	/

Gruppi elettrogeni conformi con le normative europee Stage 2 - These Diesel Generator set models are compliant with EU stage II Emission Legislation

GP33A/P	30	/	33	/	1103C-33G3	M	3	3300	41	/	6,1	/	70	1750	700	1100	780	M060	A060	T60 GP33S/P	/
GP44A/P	40	/	44	/	1103C-33TG3	M	3	3300	62	/	8	/	70	1750	700	1100	840	M060	A060	T60 GP44S/P	/
GP66A/P	60	/	66	/	1104C-44TG3	M	4	4410	83	/	10,2	/	100	2100	900	1300	940	M070	A070	T65 GP66S/P	/
GP88A/P	80	/	88	/	1104C-44TAG1	E	4	4410	110	/	14,3	/	100	2100	900	1300	1080	M070	A070	T65 GP88S/P	/
GP110A/P	100	112,5	110	125	1104C-44TAG2	E	4	4410	138	150	17,1	20,2	100	2100	900	1400	1210	M070	A070	T70 GP110S/P	/
GP145A/P	130	/	143	/	1106C-E66TAG2	E	6	6600	181	/	24,3	/	140	2850	1000	1400	1470	M070	A070	T80 GP145S/P	/
GP165A/P	150	169	165	188	1106C-E66TAG3	E	6	6600	199	219	27,5	30	140	2850	1000	1400	1500	M070	A070	T85 GP165S/P	/
GP220A/P	200	231	220	253	1306C-E87TAG3	E	6	8700	267	296	35	38,5	150	3000	1100	1500	1750	M085	A087	T85 GP220S/P	T87 GP220SM/P
GP280A/P	250	/	275	/	1306C-E87TAG6	E	6	8700	330	/	36	/	150	3000	1100	1500	1910	M087	A087	T87 GP280S/P	T90SM GP280SM/P
GP385A/P	350	/	385	/	2206C-E13TAG2	E	6	14600	473	/	52,5	/	300	3200	1300	2100	3260	M087	A087	/	T100SM GP385S/P
GP440A/P	400	/	440	/	2206C-E13TAG3	E	6	14600	531	/	60,9	/	300	3200	1300	2100	3400	M087	A087	/	T100SM GP440S/P
GP505A/P	450	/	495	/	2506C-E15TAG1	E	6	15200	605	/	73	/	300	3200	1300	2200	3430	M087	A087	T100S GP505S/P	T110SM GP505SM/P
GP560A/P	500	/	550	/	2506C-E15TAG2	E	6	15200	664	/	81	/	300	3200	1300	2200	3490	M087	A087	T100S GP560S/P	T110SM GP560SM/P
GP610A/P	550	/	605	/	2806C-E18TAG1A	E	6	18100	783	/	96	/	320	3400	1400	2200	4000	M087	A087	/	T110SM GP610SM/P
GP700A/P	650	/	715	/	2806A-E18TAG2	E	6	18130	833	/	97	/	500	3500	1600	2100	5150	M087	A087	T110S GP700S/P	T120 GP700SM/P
GP810A/P	730	/	800	/	4006-23TAG2A	E	6	22921	866	/	113	/	500	3800	1700	2250	6230	M087	A087	T110S GP810S/P	T120 GP810SM/P
GP880A/P	800	/	880	/	4006-23TAG3A	E	6	22921	1054	/	126	/	500	4000	1700	2010	6250	M087	A087	/	T130 GP880SM/P
GP1000A/P	905	/	996	/	4008TAG1A	E	8	30561	1176	/	140	/	500	4500	2000	2300	7700	M087	A087	/	T130 GP1000SM/P
GP1120A/P	1022	/	1125	/	4008TAG2A	E	8	30561	1320	/	159	/	800	5300	2100	2300	7800	M087	A087	/	T140 GP1120SM/P