

1500 rpm - 50 Hz
1800 rpm - 60 Hz
MTU

powered by



650-1250 kVA

3^{ph}



Trifase
Three phase
Triphasé
Trifásico

Aperto
Open frame
Sur châssis
Abierto

Raffreddato ad acqua
Water cooled
Refrroidi à eau
Refrigerado por agua




GP880A/M

MODELLO model	POTENZA - Power kVA				MOTORE/Engine								SERBATOIO tank	DIMENSIONI dimensions			PESO weight	QUADRO ELETTRICO electric panel		INSONORIZZATO soundproof		
	CONT. PRP		MAX LTP		MODELLO model	REG gov	CIL. cyl. N.	CILIND. displac. cc	POTENZA power cv/hp		CONSUMO consump. 75% carico load l/h			L	L w mm	A h mm		Kg	MODELLO model		MODELLO model	
	50 Hz	60 Hz	50 Hz	60 Hz					50 Hz	60 Hz	50 Hz	60 Hz							MAN key start	AUTOM automatic start	S	SM
GP700A/M	650	-	716	-	12V2000 G25TD	E	12	23880	870		109	/	500	4000	1500	1955	5150	M087	A087	T110 GP700S/M	T120 GP700SM/M	
GP880A/M	780	-	860	-	12V2000 G65TD	E	12	23880	1027		129	/	600	4500	1800	2010	5350	M087	A087	/	T130 GP880SM/M	
GP1000A/M	910	-	1005	-	16V2000 G25TD	E	16	31840	1230		147	/	800	4500	1800	2010	6250	M087	A087	/	T130 GP1000SM/M	
GP1120A/M	1005	-	1105	-	16V2000 G65TD	E	16	31840	1330		162	/	800	4700	1800	2500	7700	M087	A087	/	T130 GP1120SM/M	
GP1260A/M	1135	-	1250	-	18V2000 G65TD	E	18	35820	1480		183	/	700	4700	1800	2500	7800	M087	A087	/	T140 GP1260SM/M	

1500 rpm - 50 Hz
1800 rpm - 60 Hz
CUMMINS

powered by



636-1200 kVA

3^{ph}



Trifase
Three phase
Triphasé
Trifásico

Aperto
Open frame
Sur châssis
Abierto

Raffreddato ad acqua
Water cooled
Refrroidi à eau
Refrigerado por agua



GP1000A/C

MODELLO model	POTENZA - POWER kVA				MOTORE/Engine								SERBATOIO tank	DIMENSIONI dimensions			PESO weight	QUADRO ELETTRICO electric panel		INSONORIZZATO soundproof		
	CONT. PRP		MAX LTP		MODELLO model	REG gov	CIL. cyl. N.	CILIND. displac. cc	POTENZA power cv/hp		CONSUMO consump. 75% carico load l/h			L	L w mm	A h mm		Kg	MODELLO model		MODELLO model	
	50 Hz	60 Hz	50 Hz	60 Hz					50 Hz	60 Hz	50 Hz	60 Hz							MAN key start	AUTOM automatic start	S	SM
GP700A/C	636	681	700	750	VTA28 G5	E	12	28000	825	866	104	118	500	3500	1600	2100	5150	M087	A087	T110 GP700S/C	T120 GP700SM/C	
GP880A/C	800	909	880	1000	QSK23 G3	E	12	23150	1030	/	121	/	500	4000	1900	2010	5350	M087	A087	/	T130 GP880SM/C	
GP1000A/C	910	1029	1000	1125	QST 30 G3	E	12	30480	1200	1323	139	154	600	4300	1800	2300	7300	M087	A087	/	T130 GP1000SM/C	
GP1120A/C	1000	1138	1100	1250	QST30 G4	E	12	30480	1300	1469	151	177	800	5000	1800	2300	7700	M087	A087	/	T140 GP1120SM/C	