



GREEN POWER SYSTEMS s.r.l.
Loc Maiano Sn- 61028 CAPRAZZINO DI
SASSOCORVARO (PU) ITALY
Tel. +39 0722 726411 r.a. Fax. +39 0722 720092
E-mail: info@greenpowergen.com
www.greenpowergen.com

**Description and
technical data**

TECHNICAL DATA SHEET **GP 500 A/D**

DESCRIPTION:

1. STRUCTURE

- Model: OPEN FRAME ON SKID MOUNTED
- Engine/alternator monoblock unit coupled through flexi-disc couplings, installed on a welded steel baseframe, complete with antivibration mountings; silencer; industrial painting;
- Integrated fuel tank – 320 litres
- Fuel consumption: 195 gr/KWh
- Lead acid batteries: 24 V / 200 Ah
- Dimensions (mm): L= 3400 x W= 1800 x H= 2200 - weight (Kilos): 4200

2. MANUAL ELECTRIC START PANEL:

- Magnetothermic circuit breaker
 - Power terminal board
 - Multimeter;
 - Engine safety device: high water temperature; low oil pressure; battery charger fault; low fuel level switch;
 - Emergency stop button;
 - Fuel level;
 - Water Temperature gauge;
 - Oil gauge;
- } with manual electric panel only

TECHNICAL DATA:

1. EQUIPMENT SPECIFICATION (In accordance with ISO 8528/1)

- Standby power at cosfi 0.8 : 550 kVA
- Prime power at cosfi 0.8 : 500 kVA
- Standby power at cosfi 0.8 : 440 kW
- Prime power at cosfi 0.8 : 400 kW
- Frequency : 50 Hz
- Voltage available to the terminals : 400/230 V

2. ENGINE

- Brand and model : DEUTZ BF8M 1015 CP
- Diesel 4 stroke – water cooled – turbocharged with intercooled
- Electronic governor
- Max power : 648 Hp
- R.P.M. : 1500
- Cylinders : 8
- Displacement : 15874 cc

3. ALTERNATOR

- Brand and model : MECC-ALTE ECO40-3S (OR SIMILAR BRAND)
- Synchronous with electronic governor
- Poles : 4
- Stator/rotator insulation : class H
- Protection level : IP21
- Continuous power (50 Hz) : 500 kVA

Project manager: Ing. Lorenzo Santucci