



NOTE: GENERATING SET MUST BE LOCATED WITH, AT LEAST, ONE METER FREE SPACE AROUND FOR MAINTENANCE WORK SURFACE OF COOLING AIR INTAKE LOUVERS MUST BE, AT LEAST, TWICE SURFACE OF COOLING AIR EXHAUST LOUVERS

NOTA: EL GENERADOR DEBE SITUARSE CON, AL MENOS, UN METRO LIBRE ALREDEDOR PARA TRABAJOS DE MANTENIMIENTO LA SUPERFICIE DE REJILLA DE REFRIGERACION DE ENTRADA DEBE SER, AL MENOS, DOS VECES LA SUPERFICIE DE LA REJILLA DE SALIDA DE AIRE

MODEL/ MODELO	PRIME POWER POTENCIA	ENGINE MOTOR	ALTERNATOR ALTERNADOR	FUEL TANK (LIT.) DEPOSITO DE COMBUSTIBLE	WEIGHT (KG) PESO (KG)
GSA65D	61.0 KVA	F6L912	UCI224E	240	954

MODEL/ MODELO	AIR FLOW/CAUDALES DE AIRE (M3/H)			FUEL CONSUMPTION/ CONSUMO DE COMBUSTIBLE (L/H)		RECOMMENDED AIR FLOW FOR COMBUSTION AND COOLING/ FLUJO DE AIRE RECOMENDADO PARA COMBUSTION Y REFRIGERACION (M3/H)
	COMBUSTION	COOLING AIR	EXHAUST GASES	75% LOAD	100% LOAD	
GSA65D	216	3650	527	10.5	14.0	7000

* IF IN DOUBT-ASK, DO NOT SCALE / EN CASO DE DUDA-PREGUNTAR, NO ESCALAR
 * RECOMMENDED INSTALLATION DIMENSIONS FOR STANDARD CONFIGURATION /
 DIMENSIONES DE INSTALACION RECOMENDADAS PARA CONFIGURACION ESTANDAR
 * THE PRODUCER RESERVES THE RIGHT OF MODIFYING THE DIMENSIONS REPRESENTED IN THIS PLANE WITHOUT PRIOR NOTICE
 EL FABRICANTE SE RESERVA EL DERECHO DE MODIFICAR LAS DIMENSIONES REPRESENTADAS EN ESTE PLANO SIN PREVIO AVISO

2004	DATE	NAME		
Drawn		JCM		
Checked		JJG		
Examined				
SCALE	RECOMMENDED INSTALLATION DIMENSIONS STANDARD GENSET GSA65D - 1.500 RPM			No PIGSA65D_B00 Replacing: Replaced by: