



REF. ADS **01.00**

# ACCESSORIES | LIGHTING TOWER

Available only under request for PRAMAC Generating Sets of the range GBL 20/40 and GSL 20/40 (Soundproof).

- Suitable for Rental and Public Works.
- 6 x 1.500W halogen lamps.
- Connection of lamps by CE sockets.
- 200.000 lumen lighting capacity .
- Site trailer with four Site trailer with 4 support feet.
- Available with electric or manual lifting.
- Telescopic tower with an extension of 7,5 metres (max. 9m)
- Galvanized mobile unit (site trailer).



- Multi-Directional lighting system by quartz/iode lamps (halogen type).
- 6 x 1.500W lamps with a consumption of 12kVA.
- Lighting capacity 200.000 lumen very suitable for large surface lighting.
- Halogen lamps characterized by: intense,solar and long light.
- Protection level IP55.



- Lighting supply by socket 400V/32A CE socket.


Series GBL are supplied with a 440V/32A CE socket.  
 Series GSL are supplied with a 440V/32A CE socket. Additionally, it is advised to combine the Socket Kit (5 sockets) or Rental Kit (3 or 5 sockets) as follows:



Sockets Kit (5 sockets).	1 x 400V/63A 3P+N+T CE.	
	1 x 400V/32A 3P+N+T CE.	
	1 x 400V/16A 3P+N+T CE.	
	1 x 230V/16A 2P+T CE.	
	1 x 230V/16A Schuko.	
Rental Kit (3 or 5 sockets).	1 x 400V/63A 3P+N+T CE	-
	1 x 400V/32A 3P+N+T CE	1 x 400V/32A 3P+N+T CE
	1 x 400V/16A 3P+N+T CE	-
	1 x 230V/16A 2P+T CE	1 x 230V/16A 2P+T CE
	1 x 230V/16A Schuko.	1 x 230V/16A Schuko.



- Telescopic tower with a maximum extension of 9 metres (recommended: 7,5m).
- Available with electric or manual lifting.
- Manual turning up to 360° degrees by means of 12 work positions (1 position every 30°).



TECHNICAL CHARACTERISTICS NOT IMPREGNATIVE RESERVATION OF MODIFICATIONS FOR INNOVATION OF THE PRODUCT

TECHNICAL CHARACTERISTICS NOT IMPEGNATIVE RESERVATION OF MODIFICATIONS FOR INNOVATION OF THE PRODUCT

• Searchlights connection by retractile cable, inserted in a protective tube.



**MANUAL LIFTING VERSION:**  
Through rotating handle.



**ELECTRIC LIFTING VERSION:**  
Through push-buttons.



• **FRAME:** made of galvanized high quality steel for a maximum loading of 1.800kg.  
• **SITE TRAILER:** 1 axle, 2 wheels, hook-eye, jocket wheel and 4 telescopic supports as feets for adjustable height and reduction of risks by overturning.



**DIMENSIONS AND WEIGHT:**

**Length:** ..... 5.140 mm.  
**Width:** ..... 1.800 mm.  
**Height:** ..... 2.300 mm.  
**Weight:** ..... 607 kg (Generating Set not included).

Note: Minimum dimensions.